

Image not found or type unknown



## Tekniflex® ECA BT

Tekniflex® ECA consists of a lamination of Tekniflex® EC, a film manufactured with a minimum of 50% post consumer recycled content in the core layer, and virgin copolyester skins, and Aclar® (PCTFE) film. This product is designed for thermoformable packaging applications including cosmetic, personal care, industrial and others that are sensitive to moisture.

	Construction		WVTR 38°C, 90% RH (g/m²/d)	WVTR 38°C, 90% RH (g/100in²/d)	OTR 23°C, 50% RH (cm³/m²/d)	OTR 23°C, 50% RH (cm³/100in²/d)
ECA10200 BT	254 µm EC BT / 51 µm PCTFE	10.0 mil EC BT / 2.0 mil PCTFE	0,11	0,007	11	0,71

Available in clear, white, blue tint. Alternative EC thicknesses are available upon request.

DISCLAIMER: The information set forth in this datasheet is subject to change without notice and must be confirmed at time of purchase. No licenses, patent, or other intellectual property rights of Tekni-Plex or others are conveyed hereby. TEKNI-PLEX MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON IT. Tekni-Plex's only warranties for this product are those written warranties as may be agreed to by Tekni-Plex and its customers in a signed document. TEKNI-PLEX SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCT, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Nothing herein shall constitute or imply any promise to enter into any business relationship.

Image not found or type unknown

